

Choose Trailer Type

Then Choose Model

# Trailers- Utility Tag

Updated January 6, 2006



## LANDOLL LT1216+4



Model	Capacity*	Base Weight	Deck	Axles	Tires & Ply Rating
LT1216+4	12,000 lbs.	3,700 lbs.	20' x 8'6"	2	9.50 - 16.5



[View Photo Gallery](#)

Photos may show optional equipment

### STANDARD EQUIPMENT

<b>Load Capacity:</b>	12,000 lbs.	<b>Tilt Cylinder:</b>	2-1/2 x 16 Cushion Cylinder
<b>G.V.W.R.</b>	15,700 lbs.	<b>Approach:</b>	Full Width Landoll Traction Plate
<b>Estimated Base Weight:</b>	3,700 lbs.	<b>Lock Down:</b>	Positive Over Center
<b>Main Frame:</b>	6" Channel	<b>Lights:</b>	Sealed Beam - Per I.C.C. & Federal Regulations
<b>Crossmembers:</b>	4" Jr. I-Beam 80,000 PSI Yield on 24" Centers	<b>Electrical:</b>	6 Pole Electric Plug - Wiring in Conduit
<b>Jacks:</b>	7,000 Lb. Top Crank Bull Dog	<b>Fenders:</b>	14 Gauge - Cold Rolled Formed with Back
<b>Tires:</b>	9.50 16.5	<b>Running Boards:</b>	16 Gauge - Cold Roll formed with Anti-Skid Tape
<b>Wheels:</b>	Steel Wheels - 16.5 x 6.75-8 Bolt	<b>Tie Rings:</b>	5/8" D-Rings (6)
<b>Axles:</b>	2 - 7,000 Lb. E-Z Lubes	<b>Stake Pockets:</b>	4 Per Side
<b>Suspension:</b>	Torflex Axles	<b>Safety Chains:</b>	3/8" x 35" G70 Chain with GelCel Chargeable Battery and Box
<b>Brakes:</b>	12" x 2" Electric Brakes (Both Axles)	<b>Finish:</b>	Your Choice: White, Black or Yellow Non-Fading, Scratch & Chip Resistant Powder Coat Paint
<b>Hitch:</b>	Your Choice: 2-5/16" Ball or 3" Pintle Hook, 12" Vertical Height Adjustment-12,000 lb. Capacity		
<b>Tool Box:</b>	Under Deck		
<b>Decking:</b>	2" CA-B Copper Azole Treated Pine		
<b>Deck Height (Loaded):</b>	22"		
<b>Width:</b>	80" Inside Fenders - 102" O.A.		
<b>Length:</b>	16' Tilt Deck + 4' Stationary		
<b>Load Angle:</b>	10 Degrees		

*Specifications subject to change without notice.*

---

\*Indicates dimension may change due to options indicated.

---

## OPTIONAL EQUIPMENT

---

### **BRAKES:**

Electric Brake Kit for Truck

Hydraulic Surge Brakes in Lieu of Std (Check Local and State Regulations for Compliance)

---

### **TIE DOWN RINGS:**

Extra D-rings (Each)

---

### **DECK AND ACCESSORIES:**

Tilt Control Valve System

Sideboard per Pair

Apitong Wood (in lieu of std)

12" Centers on Crossmembers (required for forklifts)

Rumbar Decking (Requires Additional Crossmember Option)

---

### **TIRES AND RIMS:**

Spare Tire & Wheel

Spare Tire Carrier with Spare Tire & Wheel

Spare Tire Carrier

LT235/85R 16 LRG Goodyear tire in lieu of std

---

[Click here to view PDF of literature.](#)

[Click Here to receive printed literature for this product.](#)  
(Make sure you click on LT1216+4 in the product listing)

---

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562-5381

© 2002 Landoll Corporation, All rights reserved