

Choose Trailer Type

Then Choose Model

Trailers- Hydraulic

Updated March 18, 2006



LANDOLL 300A



Model	Capacity*	Deck	Axles	Tires & Ply Rating
300A-32-G	8 Ton	102	2	(8) 9.50x16.5



[View Photo Gallery](#)

Photos may show optional equipment

STANDARD EQUIPMENT

*Capacity:	16,000 Lbs.	Loaded Deck Height:	38 Inches
Deck Rating:	16,000 Lbs. In 10 Foot	Width:	102 Inches
Estimated Base Weight:	Pintle Hook 9,000 Lbs. Gooseneck 9,800 Lbs.	Decking:	1 3/8" Apitong
Main Frame:	30 Lb. 10" Structural I-Beam	Air/Electrical:	7 Way Receptacle
Crossmembers:	2"x 2" Tube	Hydraulic Hook Up:	Quick Couplers 2500 PSI/17 GPM
Slope Drop:	90 Degree	Lights:	Sealed, Potted, "LED" , grommet Mounted with Sealed Wiring Harness
Parking Stands:	Pin Drop	Finish:	Steel Grit Shot Blast to Bright Metal
Tires:	9.50 x 16.5 Radials	Powder Coat Color:	White/Black/Yellow/Blue/Red/Green
Rims:	16.5 x 6.75	Tie Downs:	(4) "P" Loops
Wheels:	8 Hole Steel Budd Type Disc	Tool Box:	Curbside (11" H x 22" D x 36" W) with Lockable Door
Axles:	2-10,000 Lb Tandem Duel Tire, Oil Bath Bearings (P/N132018 Dexter as of 6/04)	Hydraulic Winch:	Worm Gear 12,000 Lb. With 85' of 1/2" Cable.
Suspension:	5 Spring Multi Leaf	Tilt Cylinders:	1- 4" x 42" (G) or 2- 4" x 24" (P)
Brakes:	12-1/4" x 3-3/8" Electric Brakes	Undercarriage Cylinder:	1- 4" x 126"
Oil Seal Hubs:	Internal Mated Assembly	Load Angle:	7 Degree
Hitch:	Gooseneck or 5' Pintle	Accessories:	Approach Plate with Four Keyhole Tie Downs
Pin Setting:	8 1/2 Inches	Hydraulic Valve Body:	Prince Valve
Swing Clearance:	78 Inches		
Loaded Ground Clearance:	25 Inches		

*Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight rating (GAWR) or state and federal regulations.

Specifications subject to change without notice.

MODEL	A	B	C
300A-32-G	39'	32'	28' 5

*Indicates dimension may change due to options indicated.

OPTIONAL EQUIPMENT

BRAKES:

Air Brakes with 12.25" x 4" Drum Type Brakes in Lieu of Std.

- (Change made from Hayes to Dexter 6/04)

Air Over Hydraulic-Disk (for Tractor with Full Air) in Lieu of Std.

Brake Kit-Installed (Specify Truck Make/Model)

Brake Kit-Not Installed (Specify Truck Make/Model)

Low Vacuum Warning Kit-Installed

Low Vacuum Warning Kit-Not Installed

TIE DOWN RINGS:

Additional Tie-Down "P" Loop with Lynch Pin

Flush Mount "D" Rings

Recessed Mount "D" Rings

Ratchet Winch for 4" Nylon Strap - Weld On - Less Strap - One Side Rub Rail Required (Each)

HITCH:

Yolk Style Hitch in Lieu of Std.

Fifth Wheel Hitch in Lieu of Std.

2 5/16" Ball Hitch

Truck Hitch Base (Specify for Dodge) Installed

Truck Hitch Base (Specify for Dodge) Not Installed

Swivel Hitch Installation on Customer Bed (Chevy-Ford)

WINCH AND ACCESSORIES:

20,000 lb. Worm Gear Winch w/85' Cable in lieu of 12,000 lb. winch

- Standard

Wireless Remote Control - Six Function with Cross valve body

Wireless Remote Control - Six Function with Prince valve body (Orders after 03-20-06)

Wireless Remote Control - Six Function with Prince valve body (Orders before 03-20-06)

DECK AND ACCESSORIES:

Extra Side Mounted Tool Compartment

Skid Plate for Container with Formed Angle Guide 5/16" x 12" x 3 1/2"

1/8" Steel Tread Plate in Lieu of Std.

Overwidth Extensions (2-Section - 9" W x 4' L Each)

Upper Deck - 7' x 8' with 4 Tie-Down "P" Loops

HYDRAULIC POWER SOURCE:

27 H.P. Engine Package -Underslung

Air Shift PTO & Wet Kit for Tractor-Not Installed
Installation of PTO & Wet Kit (Wire Control)

TIRES AND RIMS:

Spare Budd Rim 6.75x16.5 (Wheel Only-No Tire)
Spare Tire & Rim 9.5x16.5-10 Ply Rated Radial

[Click here to view PDF of literature.](#)

[Click Here to receive printed literature for this product.](#)
(Make sure you click on 300A in the product listing)

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562-5381

© 2002 Landoll Corporation, All rights reserved