

Choose Trailer Type

Then Choose Model

Trailers- Utility Tag

Updated January 6, 2006



LANDOLL LT1220



Model	Capacity*	Deck	Axles	Tires & Ply Rating
LT1220	12,000 lbs.	20' x 8'6"	2	9.50 - 16.5



[Enlarge Photo](#)

STANDARD EQUIPMENT

Estimated Base Weight:	3,700 Lbs.	Tilt Cylinder:	2-1/2 x 16 Cushion Cylinder with Tilt Control System
Capacity	12,000 Lbs.	Approach:	Full Width Landoll Traction Plate
G.V.W.R.	15,700 Lbs	Lock Down:	Positive over Center
Main Frame:	6" Channel	Lights:	Sealed Beam - Per I.C.C. & Federal Regulations
Crossmembers:	4" Jr. I-beam 80,000 PSI Yield on 24" Centers	Electrical:	6 Pole Electric Plug - Wiring in Conduit
Jack:	7,000 Lb. Top Crank Bull Dog	Fenders:	14 Gauge - Cold Rolled Formed with Back
Tires:	9.50 16.5	Running Boards:	16 Gauge - Cold Roll Formed with Anti-Skid Tape
Wheels:	Steel Wheels - 16.5 x 6.75 -8 Bolt	Tie Rings:	5/8" D-Rings (4)
Axles:	2 - 7,000 Lbs. E-Z Lubes	Stake Pockets:	4 Per Side
Suspension:	Torflex Axles	Safety Chain:	3/8" x 35" - G70 Chain with GelCel Chargeable Battery and Box
Brakes:	12" x 2" Electric Brakes (Both Axles)	Finish:	Your Choice: White, Black or Yellow Non-Fading, Scratch & Chip Resistant "Powder Coat" Paint
Hitch:	Your Choice: 2-5/16" Ball or 3" Pintle Hook, 12" Vertical Height Adjustment - 12,000 lb. Capacity		
Tool Box:	Under Deck		
Decking:	2" CA-B Copper Azole Treated Pine		
Deck Height (Loaded):	22"		
Width	80" Inside Fenders - 102" O.A.		
Length:	20' Tilt Deck		
Load Angle:	10 Degrees		

Specifications subject to change without notice.

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562 -5381

© 2002 Landoll Corporation, All rights reserved