

Choose Trailer Type

Then Choose Model

Trailers- Detachable

Updated March 18, 2006



LANDOLL 325B



Model	Capacity*	Deck	Axles	Tires & Ply Rating
325B-48	50 Ton	24'	3	(12) 255/70R 22.5 LRH
325B-50	50 Ton	26'	3	(12) 255/70R 22.5 LRH



[Enlarge Photo](#)

STANDARD EQUIPMENT

*Capacity:	50 Ton	Gooseneck:	10 Ft. 7 Inches
Deck Rating:	100,000 Lbs. In 10 Foot	Air/Electrical:	Glad Hand/7 Way Receptacle
Estimated Base Weight:	21,500 Lbs. (48')	Hydraulic Hook Up:	Quick Couplers 2500 PSI/17GPM
Main Frame:	Fabricated 16", 100,000 PSI Flange	Lights:	Sealed, Potted, "LED", Grommet Mounted with Sealed Wiring Harness, Center Mounted Turn Signal.
Crossmembers:	8" High Tensile I-Beams on 24" Centers	Finish:	Steel Grit Shot Blast to Bright Metal
Tires:	255/70R 22.5 LRH Radial Goodyear	Powder Coat Color:	White/Black/Yellow/Blue/Red/Green
Rims:	22.5x7.50	Tie Downs:	10 "D" Rings
Wheels:	Hub Pilot/Steel Outboard Brake Drums	Tool Box:	41" W x 24" L x 10" D Between Main Frame
Axles:	3-25,000 Lb. Dual Tire, Oil Bath Bearings 49" Spacing	Lift Cylinders:	2-9"x8" Vertical Mount
Suspension:	Neway Air Ride (AR80) Yoke Mount 25,000 Lb. Capacity	Hitch:	Fifth Wheel King Pin
Brakes:	16.5x7 Full Air/ Spring Brakes	Accessories:	Fifth Wheel Type Automatic Gooseneck Lock Engagement with Lock/Unlock Visual from Tractor Cab Automatic Slack Adjusters Rail Stiffeners
Oil Seal Hubs:	Internal Mated Assembly		
Pin Setting:	15 Inches		
Swing Clearance:	84 Inches		
Loaded Ground Clearance:	8 Inches		
Loaded Deck Height:	24 Inches		
Width	102 Inches		
Decking:	2" Nominal, Apitong Track Area		

*Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

Specifications subject to change without notice.

MODEL	A	B	C
325B-48	48'	24'	44' 2 1/2
325B-50	50'	26'	46' 2 1/2

*Indicates dimension may change due to options indicated.

OPTIONAL EQUIPMENT

GOOSENECK:

12' Gooseneck with 99" Swing Clearance
 13' Gooseneck with 86" & 113" Swing Clearance
 13' Heavy Duty Gooseneck w/Provision for Flip
 52" Flip for 13' HD Gooseneck 160" Swing Clearance
 Gooseneck Weight Gage
 Fenders for 10' 7" Gooseneck
 Fenders for 12' Gooseneck
 Fenders for 13' Gooseneck
 Upper Deck-Full Width for 10' 7" Gooseneck
 Upper Deck-Full Width for 12' Gooseneck
 Upper Deck-Full Width for 13' Gooseneck
 16"x24" Two-Position Bulkhead/Front Extension (Solid)
 Halogen Work Light-Dual (Mounted on Bulkhead)
 Tool Box-Gooseneck Mounted (23" W x 15" H x 28" D)

RAMPS:

31" Front Fold Over Ramps with Traction Bars 1 Pair
 31" Front Fold Over Ramps-Wood Filled- 1 Pair
 31" Front Center Hook-on-Wood Filled (Each)
 Steel Ramps-Multiple Use (Pair)

OUTRIGGERS:

Swing out-24' Deck without Plank
 Swing out-26' Deck without Plank
 Swing out-10' Deck Extension

TRUNNION:

Front Bolsters
 Traction Bars for Front Bolster
 Boom Trough
 Boom Trough Cover (1/8" Steel Tread Plate)
 Wheel Covers-Slide In-5/16" (Per Axle)
 Removable Trunnion
 54" Axle Spacing Adds to Overall Length (Air Ride Only)
 60" Axle Spacing Adds to Overall Length (Air Ride Only)
 Flip Axle for Trailer Assembly 102" Wide (Requires Frame Reinforcement for Flip Fourth)
 Frame Reinforcement for Flip Fourth with Hinges, Pins, Electric, and Air
 Flip Third Axle in Lieu of Fixed Third Axle

Rear Deck-Full Width-for 49" Axle Spacing
Rear Deck-Full Width-for 54" Axle Spacing
Rear Deck-Full Width for 60" Axle Spacing

TIE DOWN RINGS:

Extra Flush Mounted "D" Rings

DECK AND ACCESSORIES:

96" Wide Not Available
Drop Sides-19" Loaded Deck Height
Additional Center Storage Area (10" D x 24" L x 41" W)
Lockable Hinged Cover for Storage Area
Center Filled Wood Deck-Apitong
24' Beam Deck in Lieu of Std. Full Deck
26' Beam Deck in Lieu of Std. Full Deck
24' Beam Deck in Addition to Std. (Requires Removable Trunnion)
26' Beam Deck in Addition to Std. (Requires Removable Trunnion)
10' Deck Extension-Full Width (Requires Removable Trunnion)
10' Deck Extension-Beam Deck (Requires Removable Trunnion)

SUSPENSION:

Spring Suspension Not Available
Air Raise and Lower Valve
Air Weigh Digital Scale System
Air Lift/Retract-Per Axle

HYDRAULIC POWER SOURCE:

Air Shift PTO & Wet Kit for Tractor-Not Installed (30 Gallon)
Installation of PTO and Wet Kit (Wire Control)
Hydraulic Quick Couplers 1 Male/1 Female (Matches Trailer)
Honda 11 H.P. Engine Package

TIRES AND RIMS:

255/70R 22.5 Michelin Tires in Lieu of Goodyear Tires (per axle)
Spare Goodyear Tire & Hub Pilot Type Rim (255/70R 22.5)
Spare Michelin Tire & Hub Pilot Type Rim (255/70R 22.5)
22.5 Aluminum Wheel (10 Bolt Polished) in Lieu of Std. (Each)
22.5 Aluminum Wheel (10 Bolt Machined) in Lieu of Std. (Each)
Hubometer

[Click Here to receive printed literature for this product.](#)
(Make sure you click on 325B in the product listing)

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562-5381

© 2002 Landoll Corporation, All rights reserved