

Choose Trailer Type

Then Choose Model

# Trailers- Detachable

Updated March 18, 2006



## LANDOLL 327B



Model	Capacity*	Deck	Axles	Tires & Ply Rating
327B-48	50 Ton	24'	3	(12) 255/70R 22.5 LRH



[View Photo Gallery](#)

Photos may show optional equipment

### STANDARD EQUIPMENT

<b>*Capacity</b>	50 Tons	<b>Gooseneck:</b>	10' 7"
<b>Deck Rating:</b>	100,000 Lbs. In 16 Foot	<b>Air/Electrical:</b>	7 Way Receptacle
<b>Estimated Base Weight:</b>	18,900 Lbs. (48')	<b>Hydraulic Hook Up:</b>	Quick Coupler 2500 PSI/17GPM
<b>Main Frame:</b>	Fabricated 16", 100,000 PSI Flange	<b>Lights:</b>	Sealed , Potted, "LED" Grommet Mounted with Sealed Wiring Harness
<b>Crossmembers:</b>	8" High Tensile I Beams on 24" Centers	<b>Finish:</b>	Steel Grit Shot Blast to Bright Metal
<b>Tires:</b>	255/70R 22.5 LRH Goodyear	<b>Powder Coat Color:</b>	White/Black/Yellow/Blue/Red/Green
<b>Rims:</b>	22.5x7.50	<b>Tie Downs:</b>	10 "D" Rings
<b>Wheels:</b>	Hub Pilot/Steel Outboard Brake Drums	<b>Tool Box:</b>	41" W x 24" L x 10" D Between Main Frame
<b>Axles:</b>	3-25,000 Lb. Tandem Dual Tire, Oil Bath Bearings	<b>Lift Cylinders:</b>	2-8"x8" Vertical Mount
<b>Suspension:</b>	Neway Air Ride (AR80) Yoke Mount 25,000 Lb. Capacity	<b>Hitch:</b>	Fifth Wheel King Pin
<b>Brakes:</b>	16.5x7 Full Air/Spring Brakes (Rear Axles Only) ABS, 4S2M/Center Axle Indirect	<b>Accessories:</b>	Fifth Wheel Type Automatic Gooseneck Lock Engagement with Lock/Unlock Visual from Tractor Cab, Ramp Brackets and Outrigger Brackets, Front Bolsters, Boom Trough, Automatic Slack Adjusters, Rail Stiffeners
<b>Oil Seal Hubs:</b>	Internal Mated Assembly		
<b>Pin Setting:</b>	15 Inches		
<b>Swing Clearance:</b>	84 Inches		
<b>Loaded Ground Clearance:</b>	8 Inches		
<b>Loaded Deck Height:</b>	24 Inches		
<b>Width:</b>	102 Inches		
<b>Decking:</b>	2" Nominal, Apitong Track Area		

\*Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

*Specifications subject to change without notice.*

---

MODEL	A	B	C
327B-48	48'	24'	44' 8

\*Indicates dimension may change due to options indicated.

---

## OPTIONAL EQUIPMENT

---

### GOOSENECK:

12' Gooseneck with 99" Swing Clearance  
 13' Gooseneck with 86" & 113" Swing Clearance  
 Gooseneck Weight Gauge  
 Fenders for 10' 7" Gooseneck  
 Fenders for 12' Gooseneck  
 Fenders for 13' Gooseneck  
 Upper Deck - Full Width for 10' 7" Gooseneck  
 Upper Deck - Full Width for 12' Gooseneck  
 Upper Deck - Full Width for 13' Gooseneck  
 16"/24" Two Position Bulkhead/Front Extension  
 Halogen Work Light - Dual (Mounted on Bulkhead)  
 Tool Box Gooseneck Mounted (23" W x 15" H x 28" D)

---

### RAMPS:

31" Front Fold Over Ramps with Traction Bars - 1 Pair  
 31" Front Fold Over Ramps-Wood Filled-1 Pair  
 31" Front Center Hook-On-Wood Filled (Each)  
 Beavertail-30" with Traction Bars (Adds to Trailer Length)  
 Heavy Duty Beavertail Ramps

---

### OUTRIGGERS:

Swing Out 24" Deck (Less Planks)(Capacity Not to Exceed 50% of Trailer Capacity)

---

### TRUNNION:

Boom Trough Cover 1/8" Steel Tread Plate  
 Traction Bars for Front Bolsters  
 Wheel Covers-Slide In-5/16" (Per Axle)  
 Fourth Flip Axle (Installed) (24' Deck Only)  
 - Consult Factory for Lead Time  
 60" Axle Spacing Adds to Overall Length (Air Ride Only)  
 Rear Deck-Full Width - For 49" Axle Spacing

---

### TIE DOWN RINGS:

Extra Flush Mounted "D" Rings

---

### DECK AND ACCESSORIES:

96" Width Not Available  
 Additional Center Storage Area (10" D x 24" L x 41" W)  
 Lockable Hinged Cover for Storage Area

Center Filled Wood Deck-Apitong

---

**SUSPENSION:**

Spring TR8600 Walking Beam in Lieu of Air Ride  
Air Raise and Lowering Valve  
Air Lift/Retract-Per Axle (Must Have Air Ride Suspension)  
Air Weigh Digital Scale System

---

**HYDRAULIC POWER SOURCE:**

Air Shift PTO & Wet Kit for Tractor - Not Installed  
Installation of PTO & Wet Kit  
Hydraulic Quick Couplers 1 Male/ 1 Female (Matches Trailer)  
Honda 11 H.P Engine Package

---

**TIRES AND RIMS:**

255/70R 22.5 Michelin Tires in Lieu of Goodyear Tires (per axle)  
Spare Goodyear Tire & Hub Pilot Type Rim (255/70R 22.5)  
Spare Michelin Tire & Hub Pilot Type Rim (255/70R 22.5)  
Hubometer

---

[Click Here to receive printed literature for this product.](#)  
(Make sure you click on 327B in the product listing)

---

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562-5381  
© 2002 Landoll Corporation, All rights reserved