

Choose Trailer Type

Then Choose Model

Trailers- Detachable

Updated March 17, 2006



LANDOLL 329A



Model	Capacity*	Deck	Axles	Tires & Ply Rating
329A-51	60 Ton	24'	3	(12)295/75R 22.5 LRG
329A-53	60 Ton	26'	3	(12)295/75R 22.5 LRG



[Enlarge Photo](#)

STANDARD EQUIPMENT

*Capacity	60 Ton	Decking:	2" Nominal, Apitong Track Area
Deck Rating:	120,000 Lbs. In 10 Foot	Air/Electrical:	Glad Hand/7 Way Receptacle
Estimated Base Weight:	22,500 Lbs. (51')	Hydraulic Hook Up:	Quick Couplers 2500 PSI/17GPM
Main Frame:	Fabricated 16", 100,000 PSI Flange	Lights:	Sealed, Potted, "LED", Grommet Mounted with Sealed Wiring Harness
Crossmembers:	8" High Tensile I Beams on 20" Centers	Finish:	Steel Grit Shot Blast to Bright Metal
Tires:	295/75R 22.5 LRG Radial Goodyear	Powder Coat Color:	White/Black/Yellow/Blue/Red/Green
Rims:	22.5x8.25	Tie Downs:	10 "D" Rings
Wheels:	Hub Pilot/Steel Outboard Brake Drums	Tool Box:	(41" W x 20" L x 10") D Between Main Frame
Axles:	3-25,000 Lb. Dual Tire, Oil Bath Bearings 49" Spacing	Lift Cylinders:	2-10"x8" Vertical Mount
Suspension:	Neway Air Ride AR80 25,000 Lb. Capacity	Hitch:	Fifth Wheel King Pin
**Brakes:	16.5x7 Full Air/Spring Brakes	Accessories:	Fifth Wheel Type Automatic Gooseneck Lock Engagement with Lock/Unlock, Visual From Tractor Cab, Automatic Slack Adjusters, Rail Stiffeners
Oil Seal Hubs:	Internal Mated Assembly		
Pin Setting:	15/42" Inch Dual Position		
Swing Clearance:	113 Inches (13' Neck)		
Loaded Ground Clearance:	8 Inches		
Loaded Deck Height:	24 Inches		
Gooseneck:	13' 7"		
Width:	102 Inches		

*Capacity ratings are frame capacities only. Actual load capacities may be restricted by factors such as gross axle weight ratings (GAWR) or state and federal regulations.

***ABS Not Required"

Specifications subject to change without notice.

MODEL	A	B	C
329A-51	51' 5	24'	47' 9-1/2
329A-53	53' 5	26'	49' 9-1/2

*Indicates dimension may change due to options indicated.

OPTIONAL EQUIPMENT

GOOSENECK:

13'0 Heavy Duty Gooseneck w/Provision for Flip
 52" Flip for 13' HD Gooseneck 160" Swing Clearance
 Gooseneck Weight Gauge
 Fenders for 13'0" Gooseneck
 Tool Box--Gooseneck Mounted (23" W x 15" H x 28" D)

RAMPS:

31" Front Fold Over Ramps with Traction Bars 1 Pair
 31" Front Fold Over Ramps-Wood Filled- 1 Pair
 31" Front Center Hook-On-Wood Filled (Each)
 Steel Ramps-Multiple Use (Pair)

OUTRIGGERS:

Swing Out 24' Deck without Plank
 Swing Out 26' Deck without Plank
 Swing Out 10' Deck Extension

TRUNNION:

Front Bolsters
 Traction Bars for Front Bolsters
 Boom Trough
 Boom Trough Covers (1/8" Steel Tread Plate)
 Wheel Covers-Slide in - 5/16" (Per Axle)
 Removable Trunnion
 54" Axle Spacing Adds to Overall Length (Air Ride Only)
 60" Axle Spacing Adds to Overall Length (Air Ride Only)
 Flip Axle for Trailer Assembly 8' 6" Wide
 Frame Reinforcement for Flip Fourth with Hinges, Pins Electric and Air
 Flip Third Axle in Lieu of Fixed Third Axle

TIE DOWN RINGS:

Flush Mounted "angled" D-Ring (each)
 Extra Flush Mounted "D" Rings

DECK AND ACCESSORIES:

96" Wide
 - N/A
 Drop Sides-19" Loaded Deck Height

Additional Storage Area (10" D x 24" L x 41" W)
Lockable Hinged Cover Storage Area
Center Filled Wood Deck-Apitong
24' Beam Deck in Lieu of Std Full Deck
26' Beam Deck in Lieu of Std Full Deck
24' Beam Deck in Addition to Std (Requires Removable Trunnion)
26' Beam Deck in Addition to Std (Requires Removable Trunnion)
10' Deck Extension--Full Width (Requires Removable Trunnion)
10' Deck Extension-Beam Deck (Requires Removable Trunnion)

SUSPENSION:

Spring Not Available
Air Raise and Lower Valve
Air Weigh Digital Scale System
Air Lift/Retract- Per Axle

HYDRAULIC POWER SOURCE:

Air Shift PTO & Wet Kit for Tractor-Not Installed (30 Gallon)
Installation of PTO and Wet Kit
Hydraulic Quick Couplers 1 Male/ 1 Female (Matches Trailer)
Honda 11 H.P. Engine Package

TIRES AND RIMS:

Spare Goodyear Tire (295/75R 22.5) & Hub Pilot Type Rim
Hubometer

[Click Here to receive printed literature for this product.](#)
(Make sure you click on 329A in the product listing)

[Close Window](#)

1900 North Street | Marysville, Kansas 66508 | (785) 562 -5381
© 2002 Landoll Corporation, All rights reserved