

Standard & Optional Equipment/Features - Model 330B Container Trailer

S=Standard O=Optional Blank=N/A

MODEL 330B-2	8 Ton	16,000#
MODEL 330B-1	25 Ton	50,000#
MAIN FRAME		
- Fabricated 80,000 PSI Yield Beams	S	S
- Four Beam Design	S	S
- Capacity-16,000# Distributed 10,000# Concentrated in 10'	S	
- Capacity-50,000# Distributed 20,000# Concentrated in 10'		S
KINGPIN SETTING		
- 30° Setting / 72" Swing Clearance	S	S
- 18° Setting on 90° Drop	S	S
CROSSMEMBERS		
- 3-1/2" x 3-1/2" Tube on 18" Centers	S	S
DECK & ACCESSORIES		
- 42', 48' Overall Length	O	O
- 102" Width	S	S
- 96" Width (Consult Factory)	O	O
- 42" Deck Height (Loaded)	S	S
- 1/8" Steel Tread Plate, 5" Cable Trough-Full Length, Formed Angle Skid Plate/Side 5/16" x 12" x 3-1/2"	S	S
- 12° Load Angle	S	S
- 90 Degree Drop in Lieu of Straight	O	O
- Under Deck Tool Box (23"x15"x23")	O	O
- 29" Approach Plate with (4) Keyhole Tie Downs	S	S
- 1 Pair Adjustable Container Stops	S	S
- Light for Hydraulic Controls	O	O
- Centering Boards (2 Front, 2 Rear)	O	O
WINCHES & ACCESSORIES		
- Worm Gear 12,000# w/85' of 1/2" Cable	S	S
- Worm Gear 20,000# w/85' of 5/8" Cable	O	O
- Remote Control Single Function-Street Side	O	O
- Cable Roller Guide for Winch	O	O
- Slope Roller (Recommended for 90 Degree Drop)	O	O
TIE DOWNS / CHAIN GOTCHAS		
- 4 "D" Rings - 2 Per Side, 4-4" Strap Ratchets Curbside with Opposing Hooks Street Side	S	S
- Extra Flush Mounted "D" Rings	O	O
- Extra Ratchet Winch for 4" Nylon Strap - Weld On (Less Straps)	O	O
BULKHEADS		
- 16"/24" 2 Position Bulkhead/Front Extension (Solid)	O	O
- 48" High Mesh, 102" Width	O	O
- Bolt on Binder Storage Rack for 48" Bulkheads	O	O
- Halogen Work Lights - Dual (Mounted on Bulkhead)	O	O
- Spare Tire Carrier 48" Bulkhead Front Mount	O	O
- Spare Tire Carrier 48" Bulkhead Rear Mount	O	O
- Dual Spare Tire Carrier 48" Bulkhead Front Mount	O	O

MODEL 330B-2	8 Ton	16,000#
MODEL 330B-1	25 Ton	50,000#
PARKING STANDS		
- Pin Drop	S	S
- 2 Speed Crank Down Landing Gear	O	O
AXLES		
- (1) 25,000# Tandem Dual Tire, Oil Bath Bearings	S	
- (2) 25,000# Tandem Dual Tire, Oil Bath Bearings		S
SUSPENSION		
- Transpro Mono Leaf 22,000 Lb. Capacity	S	S
- Air Ride in Lieu of Spring	O	O
- Low Load Angle 9-1/2° (48' only)	O	O
BRAKES		
- 16.5 x 7 Full Air/Spring Brakes ABS, 2S1M	S	
- 16.5 x 7 Full Air/Spring Brakes ABS, 4S2M		S
- Steel Out Board Brake Drums	S	S
OIL SEAL HUBS / RIMS		
- Internal Mated Assembly	S	S
- 22.5 x 8.25 Tubeless 10 Hole Hub Pilot Disc Type	S	S
TIRES		
- 255/70R 22.5 Goodyear LRH	S	S
- 255/70R 22.5 Michelin in lieu of Standard Goodyear	O	O
- Spare Tires and Rims Available in Standard & Optional Sizes		
WHEEL ACCESSORIES		
- Hubometer	O	O
HYDRAULIC POWER SOURCE		
- Quick Couplers/2500 PSI-17GPM	S	S
- Air Shift PTO & Wet Kit for Tractor - Not Installed	O	O
- 25 H.P. Engine Pkg (Under Deck Mounted with Cover)	O	O
- 24 H.P. Engine Pkg (Front Extension Mount)	O	O
- Engine Cover for Front Extension Mount	O	O
AIR/ELECTRICAL CONNECTION		
- Glad Hand 7 Way Receptacle	S	S
LIGHTS		
- Sealed Beam Grommet Mounted w/Sealed Wiring Harness	S	S
- Center Mounted Side Turn Signal	S	S
FINISH/COLOR		
- Steel Grit Shot Blast to Bright Metal	S	S
- Epoxy Primer	S	S
- White, Black, Yellow, Blue, Red, Green	S	S
- Acrylic Urethane	S	S
WEIGHT		
- 42' - Consult Factory		
- 48' - Consult Factory		

Pictures may show optional equipment. Specifications are subject to change due to continuous product improvements.

Delivering The Difference! Visit us at www.landoll.com



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!

L330-0400



Delivering The Difference

Model 330



LANDOLL 330

Container Trailer



Transport containers with the Rugged and Reliable Landoll 330

The Landoll Model 330 Series...

Durability with Top Performance

The Model 330 follows the design of Landoll's traveling axle family of specialty transport trailers. The Landoll container trailer is a solid, flat platform optional single drop, made with two main beams and a rugged outer channel with a 3/8" skid plate and side rail built in. The full width solid approach plate has 4 key hole tie downs. Landoll's 330 trailer is available in a single or tandem axle configuration and 42' or 48' lengths.

Operators can easily and safely load a large variety of empty storage containers. Storage rental companies have come to appreciate the strength and maneuverability of the 330. The full tilt design provides load angle versatility that allows container placement with hydraulic control at all times. The operator can adjust the load angle from 9 degrees to 17 degrees to accommodate different locations.

MODEL 330 Dimensions

		330B-1		330B-2	
A	Overall Length	42'	48'	42'	48'
B	King/Center Rear Axle	33'6"	39'6"	33'6"	39'6"
C	Axle Spacing	N/A	N/A	49"	49"
D	Front of Trailer/Kingpin	30"	30"	30"	30"
E	Swing Clearance	72"	72"	72"	72"
F	*King Pin Height	48"	48"	48"	48"
G	*Deck Height at rear	42"	42"	42"	42"

*May vary with different tractor fifth wheel heights.

Full Hydraulic Control

The 330's versatility and ease of one person operation allows safe and easy placement of containers in tight places. The hydraulic tilting and traveling axle aids the operator in placing containers right on target (next to buildings, alleyways, behind or even inside retail warehouses.) The 330 allows you to save time and maximize the number of loads to be delivered.




- Standard features such as the heavy duty side rails and centering boards easily guide the container onto the trailer deck.

Delivering the Difference...

Versatility, Maneuverability

The Landoll 330 was the first container transport trailer that was truly designed for the application of ground loading and unloading empty containers used for short term storage. The 330's versatility allows the operator to load and transport storage container lengths from 10' to 45' long. The trailer has twelve tie down locations on the main deck and six on the approach plate. The standard 12,000 lb. winch has 85' of cable that allows the operator to reach really tough loads. The standard equipment list goes on...255/70R 22.5 tires, hub pilot wheels with outboard brake drums, 16.5 x 7 full air brakes with spring brakes, ABS 2S1M on the single axle, and 4S2M on the two axle model. When looking for container trailers, a Landoll 330 will provide you with **more standard features** than any other trailer on the market. Landoll *delivers the difference* with superior manufacturing techniques, more standard features and the highest resale value in the industry today.



- The 12,000 lb. worm gear winch is standard equipment.
- Adjustable container stops offer flexibility to haul various lengths of containers.



- Heavy duty frame and undercarriage are built for many years of rugged service and strong enough to haul other rental equipment or automotive vehicles.



- Conveniently located hydraulic controls are easy to understand and provide safe operation.
- The optional self-contained engine hydraulics supply all hydraulic power needed for full operation of the trailer functions. (Not pictured)



- The rugged approach plate quickly lifts and then aligns the container for loading.



- The standard four strap winches with opposing hooks and four "D" rings tie downs are conveniently located for efficiently securing the container.