



Delivering The Difference

Model 425



LANDOLL 425

Traveling Axle Trailer

Standard & Optional Equipment/Features - Model 425 Traveling Axle Trailer

S=Standard O-Optional

MODEL 425	25 Ton	50,000#
MAIN FRAME		
- Fabricated 80,000 PSI Yield Beams	S	
- Four Beam Design	S	
KINGPIN SETTING		
- 21" Setting	S	
- 81" Swing Clearance	S	
- 5th Wheel Hitch	S	
CROSSMEMBERS		
- 4" x 4" Tube on 16" Centers	S	
- Additional Crossmembers	O	
WINCH		
- 20,000 lb. Worm Gear Winch	O	
- Wireless Remote Control	O	
- Worm Gear 12,000# Hydraulic Winch with 85' of 1/2" Cable	S	
DECK & FEATURES		
- 102" Wide	S	
- Deck Rating 30,000# in 16ft.	S	
- 90 Degree Slope Drop	S	
- 38" Deck Height (Loaded)	S	
- 1 3/8" Apitong Hardwood Deck	S	
- 8.5" Loaded Ground Clearance	S	
- Aluminum Pullouts to 13' Wide	O	
- 7.5 degree Load Angle	S	
- Lower Deck 31' Long	S	
ACCESSORIES		
- Flat Approach Plate with Four Key Hole Tie Downs	S	
- Automatic Slack Adjusters	S	
- Single Slope Roller	S	
TIE DOWNS/CHAIN GOTCHAS		
- Combination Chain Gotchas/Stake Pockets	S	
TOOL BOX		
- Twin Side Mounted in Upper Deck with Lockable Doors 6.5" H x 11.5" W x 29" D	S	
LIFT CYLINDER		
- (2) 4-1/2" x 30" Tilt Cylinders	S	
- (2) 4" x 126" Undercarriage Cylinders	S	

S=Standard O-Optional

MODEL 425	25 Ton	50,000#
PARKING STANDS		
- Pin Drop	S	
- Two Speed Landing Gear	O	
AXLES		
- (2) 25,000# Tandem Axles, Dual Tire, Oil Bath Bearings	S	
SUSPENSION		
- Neway Air Ride RLU228 22,500# Capacity	S	
- Dock Level Hyd 62,000# Capacity (NA with low pro tires)	O	
BRAKES		
- 12.25 x 7.5 Full Air/Spring Brakes ABS, 4S2M	S	
OIL SEAL HUBS		
- Internal Mated Assembly	S	
TIRES/WHEELS		
- 10R 17.5 Goodyear LRH	S	
RIMS		
- 17.5 X 6.75 Tubeless	S	
HYDRAULIC HOOK UP		
- Hydraulic Quick Couplers/2500 PSI-17GPM	S	
AIR/ELECTRICAL CONNECTION		
- 7 Way Receptacle(Electrical)	S	
LIGHTS		
- Sealed Beam Grommet Mounted w/Sealed Wiring Harness	S	
- Center Mounted Side Turn Signal	S	
FINISH/COLOR		
- Steel Grit Shot Blast to Bright Metal	S	
- Epoxy Primer	S	
- Red, Green, Blue, White, Black, Yellow, Acrylic Urethane	S	
WEIGHT (Estimated)		
- 425 - 41' 16,800#	S	
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MORE OPTIONS AVAILABLE - CONSULT FACTORY		
PICTURES MAY SHOW OPTIONAL EQUIPMENT.		



Delivering The Difference! Visit us at www.landoll.com



Call 1-800-428-5655 for your BEST hauling solutions!

1900 North Street • Marysville, KS 66508 • Ph. 785-562-5381 • FAX 785-562-4893

Remember: Quality is Always a Bargain!

L425-0602